Product datasheet

3m High cube zone 2 refrigeration/freezer Module



Key Features

- Dual temperature settings for freezer or chiller
- Temperature ranging from -24°C to +24°C
- Electronic control panel enables the adjustment of internal temperature and control of cooling plant function
- Hygienic, easy-to-clean interior
- Power hook up cable
- Double wing doors with heavy duty hinges
- Man trapped alarm for personnel safety
- Both container and sling assemblies are rated to DNV 2.7-1
- 3 phase 50HZ 380-415V, 60HZ 440-460V
- Internal cold room doors
- Rear protection gates
- Removable airflow, high grip flooring
- Internal lighting
- Removable shelving systems
- Compliant with ATEX 94/9/EC Ex II 3 G c IIB T3
- Certified for Zone 2 hazardous area

OEG extensive fleet of refrigeration and freezer solutions provide temperature controlled conditions for the transportation and storage of foodstuffs to offshore locations.

Available in a range of sizes the refrigerated units can be hooked up to the vessel or platform's own power supply.

All modules are certified in accordance with DNV 2.7-1 and EN 12079 standards and are available from our global base network. A range of optional extras and customisations can also be specified.

Options:

- Butchers door curtain
- Internal shelving
- Diesel generator
- Custom paint colour & customer logos
- GPS tracking

Specifications

Technical Specifications	
External Dimensions:	2,990mm x 2,440mm x 2,890mm
Internal Dimensions:	2,040mm x 2,090mm x 2,260mm
Tare Weight:	4,750 kg
Max. Gross Weight:	12,000 kg
Payload:	7,250 kg

Accreditations

Equipment supplied meets the specific requirements of the latest international standards & approvals DNV 2.7-1/EN 12079 or ISO 10855, SEPco, API, DOT, CFR, ASME VIII DIV 1., IMDG, ADR/RID & UK CAA CAP 43.







Can't find what you are looking for?

Contact our global sales team at **sales@oegoffshore.com** or visit our website to find your regional representative at **oeg.group**

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.