Product datasheet

# 3m High cube refrigeration/freezer module




## Key Features

- Temperature ranging from -24°C to +24°C
- Electronic control panel enables the adjustment of internal temperature and control of cooling plant function
- Power hook up cable
- Hygienic, easy-to-clean stainless steel or GRP interior
- See-through lockable control panel
- Double wing doors with heavy duty hinges
- Man trapped alarm for personnel safety
- Both container and sling assemblies are rated to DNV 2.7-1
- 3 phase 50HZ 380-415V, 60HZ 440-460V
- Internal cold room doors
- Rear protection gates
- Removable airflow, high grip flooring
- Internal lighting
- Flashing strobe beacon when unit is powered
- Low voltage 24v internal equipment

OEG's extensive fleet of refrigeration and freezer solutions provide temperature controlled conditions for the transportation and storage of foodstuffs to offshore locations.

**Available in a range of sizes the refrigerated units can be hooked up to the vessel or platform's own power supply.**

All modules are certified in accordance with DNV 2.7-1 and EN 12079 standards and are available from our global base network. A range of optional extras and customisations can also be specified.

**Options:**

- Butchers door curtain
- Internal shelving
- Diesel generator
- Custom paint colour & customer logos
- GPS Tracking
- 4 or 5 pin plug
- Temperature set prior to mobilisation

# Specifications

| Technical Specifications | |
|---|---|
| **External Dimensions:** | 2,990mm x 2,440mm x 2,890mm |
| **Internal Dimensions:** | 2,040mm x 2,090mm x 2,260mm |
| **Tare Weight:** | 4,750 kg |
| **Max. Gross Weight:** | 12,000 kg |
| **Payload:** | 7,250 kg |

## Accreditations

Equipment supplied meets the specific requirements of the latest international standards & approvals DNV 2.7-1/EN 12079 or ISO 10855, SEPco, API, DOT, CFR, ASME VIII DIV 1., IMDG, ADR/RID & UK CAA CAP 43.





## Can't find what you are looking for?

Contact our global sales team at **sales@oegoffshore.com** or visit our website to find your regional representative at **oeg.group**

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.