

Crushers

Drum crusher



OEG's **ENVIROPAK** drum crushers compact waste into 55 - 85 gallon drums before crushing the waste further. The Drum crushers can compact 55 gallon drums to 4" and reduce disposal costs of hazardous waste by compacting into UN/DOT approved drums. All units meet and exceed international MARPOL 73/78 Annex V and utilise UL listed components.



Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at oeg.group

Key features

Two handed operation for operator safety

Anvil support base to ensure drum integrity

Safety limit switch on door

Air or electric operation

UV light for sanitation

Optional features

Filter crusher / food grinder attachments available

IP56 upgrade

IECEx / ATEX component build available

Hepa filtration available

Drip pan available

Please check exact specifications with your local representative when ordering.

Imperial | International/US standard

Unit model	Model MPC40	Model MPC60	Model MPC85
Capacity	55 gal.	55 gal.	85 gal.
Dimensions (HxWxD - in)	104 x 39 x 38"	118 x 48 x 39"	113 x 54 x 46"
Deck space	10 ft ²	13 ft ²	17 ft ²
Weight	1,615 lbs	1,840 lbs	3,100 lbs
Compaction force	30,000 lbs	60,000 lbs	85,000 lbs
Electrical rating	3HP 230/460V 7.8 / 2.9 AMP	5HP 230/460V 15.5 / 7.8 AMP	10HP 230/460V 26.8 / 13.4 AMP

Product datasheet

Crushers

Drum crusher

Imperial | International/US standard

Unit model	Model MPC40	Model MPC60	Model MPC85
Air requirement	100PSI / 175 CFM	100PSI / 175 CFM	100PSI / 175 CFM
Cycle time	60 seconds	96 seconds	75 seconds
Oil capacity	10 gal	10 gal	10 gal
In drum compaction	Yes	Yes	Yes
Drum compaction	No	Yes	Yes

Metric | International standard

Unit model	Model MPC40	Model MPC60	Model MPC85
Capacity	208 litres	208 litres	321 litres
Dimensions (HxWxD - mm)	2,641 x 990 x 965 mm	2,997 x 1,219 x 990 mm	2,870 x 1,372 x 1,168 mm
Deck space	1.0 m ²	1.2 m ²	1.6 m ²
Weight	733 kg	835 kg	1,406 kg
Compaction force	13,607 kg	27,215 kg	38,555 kg
Electrical rating	3HP 230/460V 7.8 / 2.9 AMP	5HP 230/460V 15.5 / 7.8 AMP	10HP 230/460V 26.8 / 13.4 AMP
Air requirement	100PSI / 175 CFM	100PSI / 175 CFM	100PSI / 175 CFM
Cycle time	60 seconds	96 seconds	75 seconds
Oil capacity	37.8 litres	37.8 litres	37.8 litres
In drum compaction	Yes	Yes	Yes
Drum compaction	No	Yes	Yes

Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

