

Chemical injection pump

Pump units



Key features

All stainless steel

Air controls of air filter / regulator / gauge / on-off control valve

NPT or Autoclave outlet complete with gauge and manually adjusted pressure relief valve

OEG's **BLUEMANTA** portable pressure test units are available in various sizes and pressure ratings. They can be supplied as a standalone PTU, with a circular chart recorder, or a digital recording device incorporated. The pump is an air-driven liquid unit capable of handling various pressures, volumes, and fluids. All units are supplied piped and mounted in a boxed section stainless steel frame with colour coded mimic panel. Various items of pressure test equipment designed for use with the pump units can also be supplied such as high pressure hoses and manifolds.

Metric | International standard

Model no.	Dimensions (H x W x D) mm	Max working pressure	Tank capacity	Max flow
05-CI	790 x 580 x 600	ASF-100 = 9,000 psi ASF-150 = 13,500 psi	48 L	1.5 L/min

Imperial | International/US standard

Model no.	Dimensions (H x W x D) mm	Max working pressure	Tank capacity	Max flow
05-CI	31.1" x 22.8" x 23.6"	ASF-100 = 9,000 psi ASF-150 = 13,500 psi	12.7 Gal	0.4 Gal/min

Please check exact specifications with your local representative when ordering.

Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at oeg.group

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

