

Waste compactors

H-series



Key features

- Stainless steel
- Air or electric operation
- Door safety switch and two-hand operation for operator safety
- In-bag compaction at a 5:1 safety ratio
- Slow-release door for easy bag removal
- UV light for sanitation

Optional features

- Filter crusher / food grinder attachments available*
- IP56 upgrade
- IECEx / ATEX component build available*
- Baling capabilities*

* Not available for Model H2
Please check exact specifications with your local representative when ordering.

OEG's patented **ENVIROPAK** H-series compactors are designed to compact all types of non-hazardous waste and can be modified to process medical waste. The compactors improve shipboard incinerator efficiency and reduce operating time by compacting waste prior to incineration. All compactors meet and exceed international MARPOL 73/78 Annex V and use UL listed components.



Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at oeg.group

Imperial International/US standard				
Unit model	Model H2	Model H5	Model H10	Model H15
Capacity	6 ft ³	20 ft ³	40 ft ³	50 ft ³
Dimensions (HxWxD - in)	79 x 32 x 27"	91 x 48 x 49"	120 x 52 x 51"	128 x 54 x 56"
Deck Space	6 ft ²	15 ft ²	19 ft ²	21 ft ²
Weight	520 lbs	1,615 lbs	1,930 lbs	2,100 lbs
Compaction Force	10,000 lbs	28,000 lbs	40,000 lbs	40,000 lbs

Waste compactors

H-series

Imperial | International/US standard

Unit model	Model H2	Model H5	Model H10	Model H15
Bag Model	HV96033	HV96025	HV96030	HV96027
Bag SWL	650 lbs	1000 lbs	2,200 lbs	2,200 lbs
Electrical Rating	2HP 110/230/480V 14/5.8/2.9 AMPS	3HP 230/460V 7.8/2.9 AMPS	5HP 230/460V 15.5/7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS
Air Requirement	100PSI / 175 CFM	100PSI / 175 CFM	100PSI / 175 CFM	100PSI / 175 CFM
Cycle Time	35 seconds	50 seconds	95 seconds	95 seconds
Oil Capacity	1.5 GAL	2.5 GAL	10 GAL	10 GAL

Metric | International standard

Unit model	Model H2	Model H5	Model H10	Model H15
Capacity	0.2 m ³	0.57 m ³	1.1 m ³	1.4 m ³
Dimensions (HxWxD - mm)	2,007 x 813 x 686 mm	2,311 x 1,194 x 1,219 mm	3,048 x 1,321 x 1,295 mm	3,251 x 1,372 x 1,422 mm
Deck Space	0.6 m ²	1.4 m ²	1.8 m ²	2 m ²
Weight	236 kg	733 kg	876 kg	952 kg
Compaction Force	4,536 kg	12,701 kg	18,144 kg	18,144 kg
Bag Model	HV96033	HV96025	HV96030	HV96027
Bag SWL	295 kg	454 kg	997 kg	997 kg
Electrical Rating	2HP 110/230/480V 14/5.8/2.9 AMPS	3HP 230/460V 7.8/2.9 AMPS	5HP 230/460V 15.5/7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS
Air Requirement	100PSI / 175 CFM	100PSI / 175 CFM	100PSI / 175 CFM	100PSI / 175 CFM
Cycle Time	35 seconds	50 seconds	95 seconds	95 seconds
Oil Capacity	5.6 L	9.5 L	38 L	38 L

Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

