

Waste compactors

M-series



OEG's **ENVIROPAK** M-series compactors offer safe, simple, and reliable waste management solutions. Featuring a large loading door and integrated drip pan, they handle all types of waste efficiently while minimising mess. Safety is prioritised with a latch door designed for gradual release and a hydraulic system equipped with a relief valve. Each unit undergoes sandblasting to white metal, is zinc-coated, and seal-welded to ensure durability and resistance to corrosion.



Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

Key features

- Compacts all types of waste
- Large load door for bulk handling (34 x 24")
- Waste bags ejected hydraulically for easy removal
- Hoses rated to 16,000 psi
- Enclosed drip pan
- In-bag compaction at a 5:1 safety ratio

Optional features

- Filter crusher / food grinder attachments available
- IP56 upgrade
- IECEX / ATEX component build available

Please check exact specifications with your local representative when ordering.

Imperial International/US standard			
Unit model	Model 20M	Model 40M	Model 50M
Capacity	20 ft ³	40 ft ³	50 ft ³
Dimensions (HxWxD - in)	90 x 39 x 43"	118 x 56 x 52"	124 x 58 x 54"
Deck space	12 ft ²	18 ft ²	22 ft ²
Weight	2,320 lbs	2,450 lbs	-
Compaction force	28,000 lbs	40,000 lbs	60,000 lbs

Product datasheet

Waste compactors

M-series

Imperial | International/US standard

Unit model	Model 20M	Model 40M	Model 50M
Bag model	HV96025	HV96030	HV96027
Bag SWL	1,000 lbs	2,200 lbs	2,200 lbs
Electrical rating	5 HP 230 / 460V 15.5 / 7.8 AMPS	5 HP 230 / 460V 15.5 / 7.8 AMPS	5 HP 230 / 460V 15.5 / 7.8 AMPS
Air requirement	100PSI / 175CFM	100PSI / 175CFM	100PSI / 175CFM
Cycle time	35 seconds	45 seconds	-
Oil capacity	-	-	10 Gal

Metric | International standard

Unit model	Model 20M	Model 40M	Model 50M
Capacity	0.57 m ³	1.14 m ³	1.42 m ³
Dimensions (HxWxD - mm)	2,286 x 991 x 1,093 mm	2,997 x 1,423 x 1,321 mm	3,150 x 1,473 x 1,372 mm
Deck space	1.12 m ²	1.68 m ²	2.04 m ²
Weight	1,053 kg	1,112 kg	-
Compaction force	12,700 kg	18,143 kg	27,240 kg
Bag model	HV96025	HV96030	HV96027
Bag SWL	454 kg	999 kg	999 kg
Electrical rating	5 HP 230 / 460V 15.5 / 7.8 AMPS	5 HP 230 / 460V 15.5 / 7.8 AMPS	5 HP 230 / 460V 15.5 / 7.8 AMPS
Air requirement	100PSI / 175CFM	100PSI / 175CFM	100PSI / 175CFM
Cycle time	35 seconds	45 seconds	-
Oil capacity	-	-	38 L

Can't find what you are looking for?

Contact our global sales team at sales.enviropak@oeg.group or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

