

# Waste compactors

## Rollback series



OEG's **ENVIROPAK** rollback series compactors provide safe, simple, and reliable solutions for compacting non-hazardous waste. Operator safety is prioritised with all moving parts being completely enclosed, while the hydraulically operated slow-release door ensures efficient waste removal and a drip pan ensures clean removal of any excess liquid. Drum crushing is seamlessly performed within the chamber without the need for an adaptor.



### Can't find what you are looking for?

Contact our global sales team at [sales.enviropak@oeg.group](mailto:sales.enviropak@oeg.group) or visit our website to find your regional representative at [oeg.group](http://oeg.group)

Imperial   International/US standard				
Unit model	Model 1200RB	Model 3000RB	Model 4000RB	Model 5000RB
Capacity	12 ft <sup>3</sup>	30 ft <sup>3</sup>	40 ft <sup>3</sup>	50 ft <sup>3</sup>
Dimensions (HxWxD - in)	112 x 48 x 64"	113 x 51 x 92"	113 x 60 x 91"	111 x 62 x 93"
Deck space	24 ft <sup>2</sup>	31 ft <sup>2</sup>	35 ft <sup>2</sup>	35 ft <sup>2</sup>
Weight	1,830 lbs	3,030 lbs	3,800 lbs	4,010 lbs
Compaction force	38,000 lbs	60,000 lbs	60,000 lbs	60,000 lbs

## Key features

- Compacts all non-hazardous waste
- Air or electrically operated
- Hydraulic operated roll back top for easy loading and unloading
- 2" deep drip pan with drain
- In-bag compaction at a 5:1 safety ratio
- Crusher available

## Optional features

- Filter crusher / food grinder attachments available
- IP56 motor upgrade
- IECEx / ATEX component build available

Please check exact specifications with your local representative when ordering.

## Product datasheet

# Waste compactors

## Rollback series

Imperial | International/US standard

Unit model	Model 1200RB	Model 3000RB	Model 4000RB	Model 5000RB
Bag model	HV96021	HV96026	HV96030	HV96027
Bag SWL	600 lbs	1,500 lbs	2,200 lbs	2,200 lbs
Electrical rating	5HP 230 / 460 V 15.5, 7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS
Air requirement	100PSI / 175 CFM	100PSI / 175CFM	100PSI / 175CFM	100PSI / 175CFM
Cycle time	50 seconds	60 seconds	60 seconds	60 seconds
Oil capacity	7 gal	10 gal	10 gal	10 gal

Metric | International standard

Unit model	Model 1200RB	Model 3000RB	Model 4000RB	Model 5000RB
Capacity	0.34 m <sup>3</sup>	0.85 m <sup>3</sup>	1.14 m <sup>3</sup>	1.42 m <sup>3</sup>
Dimensions (HxWxD - mm)	2,845 x 1,219 x 1,626	2,692 x 1,299 x 2,337 mm	2,871 x 1,524 x 2,312 mm	2,820 x 1,575 x 2,337 mm
Deck space	2.23 m <sup>2</sup>	2.88 m <sup>2</sup>	3.25 m <sup>2</sup>	3.25 m <sup>2</sup>
Weight	830 kg	1,377 kg	1,724 kg	1,822 kg
Compaction force	17,252 kg	27,216 kg	27,216 kg	27,216 kg
Bag model	HV96021	HV96026	HV96030	HV96027
Bag SWL	272 kg	681 kg	999 kg	999 kg
Electrical rating	5HP 230 / 460 V 15.5, 7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS	5HP 230/460V 15.5/7.8 AMPS
Air requirement	100PSI / 175 CFM	100PSI / 175CFM	100PSI / 175CFM	100PSI / 175CFM
Cycle time	50 seconds	60 seconds	60 seconds	60 seconds
Oil capacity	26 L	38 L	38 L	38 L

### Can't find what you are looking for?

Contact our global sales team at [enviropak.sales@oegoffshore.com](mailto:enviropak.sales@oegoffshore.com) or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

