

# Food grinders

## Tuff gut II



OEG's **ENVIROPAK** Tuff gut II food grinders are designed for galley installation, but are suitable to withstand outdoor elements, built with an all stainless-steel structure and grinding components. The Tuff gut II is delivered ready to connect to the water supply, discharge and power supply for easy setup. All units meet and exceed international MARPOL 73/78 Annex V and IP55 protection class.



### Can't find what you are looking for?

Contact our global sales team at [sales.enviropak@oeg.group](mailto:sales.enviropak@oeg.group) or visit our website to find your regional representative at [oeg.group](http://oeg.group)

Imperial   International/US standard		
Unit model	5 gallon sink	45 gallon sink
Hopper capacity	5 gal.	45 gal.
Dimensions (HxWxD - in)	41 x 31 x 26"	62 x 40 x 41"
Deck space	5,6 ft <sup>2</sup>	11,4 ft <sup>2</sup>
Weight	350 lbs.	700 lbs.
Requirements	240 or 480 vac / 3 ph / 50 or 60 hz	240 or 480 vac / 3 ph / 50 or 60 hz
Electrical rating	5, 7,5, 10, 15 HP 230 / 460 V 15,5 / 7,8 Amps	10, 15, 20 HP 230 / 460 V 15,5 / 7,8 Amps
Load capacity	200 gallons / hr	400 gallons / hr

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.

## Key features

- Safety switch on hopper lid prevents operation unless lid is closed
- Range of HP motor options
- Hopper flusing nozzle
- Custom sink sizes and motors
- Undersink or worktable models
- Automatic operation with timer feature

## Optional features

- IP56 upgrade
- IECEx / ATEX component build available
- Magnetic catch guard to prevent accidental loss of silverware
- Environmentally friendly
- Enz-Odours odour remover

Please check exact specifications with your local representative when ordering.

## Product datasheet

# Food grinder

## Tuff gut II

Imperial | International/US standard

Unit model	5 gallon sink	45 gallon sink
Discharge	2" male camlock	2" male camlock
Water inlet	0.5" female pipe	0.5" female pipe

Metric | International standard

Unit model	5 gallon sink	45 gallon sink
Hopper capacity	19 litres	170 litres
Dimensions (HxWxD - mm)	1,044 x 805 x 652 mm	1,579 x 1,019 x 1,036 mm
Deck space	0.5 m <sup>2</sup>	1 m <sup>2</sup>
Weight	159 kg	318 kg
Requirements	240 or 480 vac / 3 ph / 50 or 60 hz	240 or 480 vac / 3 ph / 50 or 60 hz
Electrical rating	5, 7.5, 10, 15 HP 230 / 460 V 15.5 / 7.8 Amps	10, 15, 20 HP 230 / 460 V 15.5 / 7.8 Amps
Load capacity	750 litres / hr	1500 litres / hr
Discharge	50.8 mm male camlock	50.8 mm male camlock
Water inlet	12.7mm female pipe	12.7mm female pipe

### Can't find what you are looking for?

Contact our global sales team at [sales.enviropak@oeg.group](mailto:sales.enviropak@oeg.group) or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

