

ISO tanks



Standard ISO tanks are used for the transportation and storage of bulk liquids and are designed and manufactured to meet ADR/RID, US DOT CFR49, UK DETR, UIC, TIR, CSC, AAR600, TC, IMDG, TIR, CFR 49, ISO, and T11 standards. Our standard fleet is available from our global network of locations on a sale or rental basis.

Key features

Steam heating
Insulation and cladding

Optional features

Drop frame chassis
Remote closures
Fittings to customer specifications
Remote fluid level monitoring/GPS Tracking
Fall protection

Please check exact specifications with your local representative when ordering.

Metric | International standard

Type	External dimensions (LxWxH - mm)	Tare weight (kgs)	Payload (kgs)	Max gross weight (kgs)
20ft Standard ISO tank	6,096 × 2,438 × 2,743	4,600	25,880	30,480
24,000 Litre ISO tank	6,096 × 2,438 × 2,591	3,600	32,400	36,000

Imperial | International/US standard

Type	External dimensions (LxWxH - ft/in)	Tare weight (lbs)	Payload (lbs)	Max gross weight (lbs)
20ft Standard ISO tank	20' × 8' × 9'	10,141	57,055	67,196
24,000 Litre ISO tank	20' × 8' × 8'7"	7,937	71,429	79,366

Can't find what you are looking for?

Contact our global sales team at sales@oegoffshore.com or visit our website to find your regional representative at oeg.group

E & OE – All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.