

Single pump unit

Pump units



Key features

All stainless steel

Air controls of air filter / regulator / gauge / on-off control valve

NPT or Autoclave outlet complete with gauge and manually adjusted pressure relief valve

Optional nVision reference recorder attachment

Please check exact specifications with your local representative when ordering.

OEG's BlueManta portable pressure test units are available in various sizes and pressure ratings. They can be supplied as a standalone PTU, with a circular chart recorder, or a digital recording device incorporated. The pump is an air-driven liquid unit capable of handling various pressures, volumes, and fluids. All units are supplied piped and mounted in a boxed section stainless steel frame with colour coded mimic panel.

Various items of pressure test equipment designed for use with the pump units can also be supplied such as high pressure hoses and manifolds.

Specifications		Pump size				Liquid pump information			
		10K	15K	20K	30K				
Model no.	05-SPU					Model	ASF 150	HSF 225	
Dimensions (H x W x D)	580 x 562 x 404 mm (22.8" x 22.1" x 15.9" in)	MWP	7.5K	11.25K	15K	22.5K	Unit compatibility	10K, 15K, 20K	30K
Dimensions w/ optional nVision (H x W x D)	714 x 562 x 404 mm (28.1" x 22.1" x 15.9" in)	Chart recorder	10K	15K	20K	30K	HP	1.5	1.5
		nVision reference recorder	10K	15K	-	-	Actual ratio	173	260
							Displacement	0.27 (cu/in) 4.5 (cu/ml)	0.18 (cu/in) 3.0 (cu/ml)
							Outlet pressure	15,000 (psi) 1,034 (bar)	30,000 (psi) 2,069 (bar)
							Outlet flow	81 (cu/in/min) 1.3 (l/min)	41 (cu/in/min) 0.7 (l/min)

Can't find what you are looking for?

Contact our global sales team at rentals.bluemanta@oeg.group or visit our website to find your regional representative at oeg.group

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.