

# Spooling units



OEG's BlueManta spooling units are designed to run control lines into wells. By creating back tension, the line is kept tight and prevents the spool from free running. All spooling units are manufactured and designed in accordance with DNV 2.7-1 and EN12079 standards, and are fully guarded to meet PUWER Regulations.

### Can't find what you are looking for?

Contact our global sales team at [rentals.bluemanta@oeg.group](mailto:rentals.bluemanta@oeg.group) or visit our website to find your regional representative at [oeg.group](http://oeg.group)

## Key features

- Various standard and bespoke designs available
- Hand held or remote control panel
- Quick release shaft
- Forklift pockets

## Accessories

- Hydraulic rotary and electric slip ring
- Mechanically driven winder system for neat spooling of line
- Stacked units available for two spools at once

Please check exact specifications with your local representative when ordering.

Type	Model No	Maximum drum dimensions (in)			External dimensions			Weights Kgs		
		Diameter	Width	Shaft	L	W	H	Tare	SWL	Gross
<b>30" Spooling unit</b>	02-3000	32"	18"	3"	3'5" (1060mm)	3'3" (1020mm)	4'4" (1360mm)	600	900	1,500
<b>36" Spooling unit</b>	02-3600	36"	30"	3"	4'9" (1500mm)	3'9" (1200mm)	4'7" (1435mm)	700	1,300	2,000
<b>44" Spooling unit</b>	02-4000	44"	36"	3"	5'3" (1630mm)	4'4" (1350mm)	5'2" (1595mm)	1,000	3,500	4,500
<b>50" Spooling unit</b>	02-5000	50"	48"	3"	6'7" (1985mm)	5' (1535mm)	6' (1825mm)	1,200	5,000	6,200
<b>55" Spooling unit</b>	02-5500	55"	48"	3"	6'5" (1985mm)	5'4" (1650mm)	6' (1840mm)	1,300	7,200	8,500
<b>65" Spooling unit</b>	02-6500	65"	48"	3"	7'1" (2162mm)	6'3" (1950mm)	6'8" (2060mm)	1,600	8,400	10,000
<b>75" Spooling unit</b>	02-7500	75"	57"	3 or 4"	8' (2435mm)	7'5" (2275mm)	7'9" (2400mm)	2,000	9,000	11,000

# Spooling units

Metric | International standard

Type	Model No	Maximum drum dimensions (in)			External dimensions			Weights Kgs		
		Diameter	Width	Shaft	L	W	H	Tare	SWL	Gross
82" Spooling unit	02-85WD	82"	62"	4"	9'2" (2800mm)	7'9" (2350mm)	7'4" (2226mm)	2,500	10,000	12,500
85" Spooling unit	02-8500	85"	62"	4"	9'2" (2800mm)	8'2" (2500mm)	8'3" (2550mm)	2,500	10,000	12,500
96" Spooling unit	02-9600	96"	65"	4"	10'3" (3140mm)	9'2" (2800mm)	9'8" (2940mm)	2,500	12,000	14,500
96" Spooling unit (13 Tonnes)	02-9600-13T	96"	65"	4"	10'3" (3140mm)	9'2" (2800mm)	9'8" (2994mm)	3,000	13,000	16,000
	HR-9600				10'3" (2982mm)	9'2" (2982mm)	9'8" (2870mm)	2,500	10,000	12,500
	02-9600-XL	96"	75"	4.5"	10'3" (3000mm)	9'2" (2800mm)	9'8" (2808mm)	3,500	17,500	21,000

## Can't find what you are looking for?

Contact our global sales team at [rentals.bluemanta@oeg.group](mailto:rentals.bluemanta@oeg.group) or visit our website to find your regional representative at [oeg.group](https://www.oeg.group)

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units with your local representative when ordering.

